



## REVERSE

The ultimate solution for laminated glass grinding



[www.fritzsching.de](http://www.fritzsching.de)



Premium grinding tools since 1919  
[www.tyrolit.com](http://www.tyrolit.com)

# REVERSE

## The ultimate solution for laminated glass grinding.

REVERSE wheels have been designed to improve the productivity of machinery for processing of laminated glass for architectural and structural facades.

**+ Improvement of diamond tool life up to 30%:** By using REVERSE tools, the removal of plastic shards after grinding is easy and effective. This reduces frictions while grinding and prevents deformation and wear of diamond wheels.

**+ Increased working speed:** The new REVERSE wheels allow a 20% faster working speed compared to standard ones.



**+ Enhanced edge finishing quality:** Through a regular and effective removal of plastic shards, the diamond band is always free of process waste and can work with no overheat. This ensures enhanced finishing quality of the edge.

**+ Fragmentation of plastic waste:** REVERSE tools ensure a fragmentation of plastic waste into small shards that can easily drain away from the grinding area (picture B). This avoids machine stops and re-setting during process. Moreover it solves the problem of scheduled cleaning cycles to remove plastic waste (picture A).

## TYROLIT suggested parameters for REVERSE wheels:

Ø	Wheel description	glass thickness	RPM	max feed rate	max removal
100 mm	Rough segmented wheel	C6 / C8	5500 rpm	6000 mm/min	1,00 mm
		C10 / C12	5500 rpm	5500 mm/min	1,50 mm
		C16 / C20	5500 rpm	5000 mm/min	2,00 mm
	Medium TPZ cont. Band wheel	C6 / C12	5500 rpm	7000 mm/min	1,00 mm
		C16 / C20	5500 rpm	6000 mm/min	1,00 mm
		Fine TPZ cont. Band wheel	C6 / C20	5500 rpm	5000 mm/min
150 mm	Rough segmented wheel	C6 / C8	5000 rpm	7000 mm/min	1,00 mm
		C10 / C12	5000 rpm	7000 mm/min	1,50 mm
		C16 / C20	5000 rpm	6000 mm/min	2,00 mm
	Medium TPZ cont. Band wheel	C6 / C12	5000 rpm	7000 mm/min	1,00 mm
		C16 / C20	5000 rpm	6000 mm/min	1,00 mm
		Fine TPZ cont. Band wheel	C6 / C20	5000 rpm	5000 mm/min
200 mm	Rough segmented wheel	C6 / C8	3600 rpm	7000 mm/min	1,00 mm
		C10 / C12	3600 rpm	7000 mm/min	1,50 mm
		C16 / C20	3600 rpm	6000 mm/min	2,00 mm
	Medium TPZ cont. Band wheel	C6 / C12	3600 rpm	7000 mm/min	1,00 mm
		C16 / C20	3600 rpm	6000 mm/min	1,00 mm
		Fine TPZ cont. Band wheel	C6 / C20	3600 rpm	5000 mm/min



Picture A



Picture B

**TYROLIT VINCENT S.R.L.**

Via dell' Elettronica 6 | 36016 Thiene | Italy | Tel.: +39 0445 359911 | Fax: + 39 0445 370842 | E-Mail: glass@tyrolit.com

**Vertrieb für Deutschland & Schweiz:**

**W. Fritzsching GmbH & Co. KG**

Nadlerstr. 20 | 88299 Leutkirch | Germany | Tel +49 (0)7561 8487 - 0 | www.fritzsching.de | information@fritzsching.de